

Crosby® Grade 100 Foundry Hooks

Fatigue Rated®

"QT"
QUENCHED & TEMPERED

QUIC-CHECK®


Crosby 8/10™

A-1359



- Forged Alloy Steel - Quenched and Tempered.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Each hook has a Product Identification Code (PIC) for material traceability, along with the size and the name Crosby & U.S.A. in raised letters.
- Suitable for use with Grade 100 chain in overhead lifting applications as long as hook is Proof Tested as part of the chain sling assembly or as an individual component. Per ANSI B30.9-1.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color - Crosby Grade 100 Alloy Products."

A-1359 Clevis Foundry Hook



Chain Size		Working Load Limit (lbs.)*	A-1359 Stock No.	Weight Each (lbs.)	Dimensions (in.)							
(in.)	(mm)				A	C	D	F	G	K	N	AA
1/4	7	4300	1049907	2.10	6.26	4.39	4.82	2.50	1.13	0.88	1.57	3.50
5/16	8	5700	1049911	2.10	6.26	4.37	4.82	2.50	1.13	0.88	1.57	3.50
3/8	10	8800	1049916	4.29	7.76	5.54	5.82	3.00	1.38	1.30	1.88	4.00
1/2	13	15000	1049925	7.93	9.38	6.67	7.04	3.50	1.63	1.50	2.25	4.50
5/8	16	22600	1049934	14.2	11.25	7.68	8.17	4.00	2.19	1.75	2.53	5.00
3/4	18-20	35300	1049943	24.7	14.43	9.79	9.65	5.00	2.40	2.20	3.39	6.00
7/8	22-23	44100	1049952	43.8	16.25	11.02	11.03	5.51	3.07	2.72	3.74	6.50

* Ultimate Load is 4 times the Working Load Limit.