

Grade 80 Alloy Chain

SPECTRUM 8® ALLOY CHAIN



- Alloy Steel.
- Heat Treated.
- Finish – Black rust preventative coating.
- Permanently embossed with manufacturer’s marking and 8 (Grade).
- Proof Tested at 2 times the Working Load Limit with certification.
- Standard container – Steel drum up to 16 mm & wood boxes above 18 mm.

Grade 80 Alloy Chain Recommended for Overhead Lifting Applications

Chain Size (mm)	Spec. 8 Drum Stock No.	Meters Per Drum	Dimensions (mm)	Working Load Limit (t)*	Weight Per Meter (kg)
6	1244915	200	6 x 18	1.1	.80
7	1244985	200	7 x 21	1.5	1.05
8	1245055	200	8 x 24	2.0	1.25
10	1245125	200	10 x 30	3.2	2.20
13	1245195	150	13 x 39	5.3	3.80
16	1245265	100	16 x 48	8.0	5.70
18	1245305	50	18 x 54	10.0	7.30
19	1245356	50	19 x 57	11.2	8.03
20	1245396	50	20 x 60	12.5	9.00
22	1245426	50	22 x 66	15.0	10.90
23	1245453	50	23 x 69	16.0	10.90
26	1245496	50	26 x 78	21.2	15.20
32	1245514	20	32 x 96	31.5	23.00

* Proof loaded at 2 times Working Load Limit. Ultimate Load is 4 times the Working Load Limit.

Crosby provides two methods of attaching Spectrum 8® chain to Crosby fittings.



A-1337
LOK-A-LOY®
Connecting Link
Refer to Page 221



S-1325
Grade 100
Coupler Link
Refer to page 231