



**680**  
Construction Block  
with Shackle



**680**  
Construction Block  
with Hanger



**680**  
Construction Block  
Bolt only



## 680 Construction Blocks

- Wide Range of products available.
- Capacity: 5 to 100 Tons – Larger models available.
- Sheave sizes: 6” to 24” O.D.
- Wireline Sizes: 3/8” to 1-1/4”
- Equipped with genuine Crosby® forged steel, Quenched and Tempered shackles that contain the patented **QUIC-CHECK®** markings.
- Design Factor of 4:1.
- All 680 Series Blocks are furnished standard with Bronze Bushings.
- All 680 blocks 16” and larger, are furnished with McKissick® Roll-Forged sheaves with flame hardened grooves
- Sheaves are lubricated through center pin, with a separate lube channel to each bearing.
- Single sheave blocks have thimble dead end.
- Manufactured by an ISO 9001 and API Q1 Certified facility .
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.

### OPTIONS AVAILABLE

- Roller bearing sheaves
- Hanger and Bolt Only models available
- Third party testing with certification
- Galvanized finish – Most model