

Shipbuilding Clamps: Shipsections

IPSBUUZ



The IPSBU(U)Z shipbuilding clamps are used for the lifting, transfer and placing of complete shipsections. These clamps are fitted with a locking device for both open and closed positions, which ensures complete reliability. They are to be used exclusively for bulb profiles (not for plates).

For the lifting, transfer and placing of complete shipsections

- Available in capacities of 4.5 thru 22.50 metric tons.
- Wide variety of jaw openings available: HP 4.00" to HP 17.00".
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Company name (CrosbyIP), logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. Serial number is included on the test certificate with maintenance and warranty logbook.
- Optional IP-5000 Stinger assembly available (see page 420). Allows for easy connection between the clamp and hoist hook.
- Maintenance replacement parts are available.
- Manufactured by a ISO 9001 facility.
- All sizes are **RFID EQUIPPED**.



Load Rated

Model IPSBUUZ and IPSBUSUZ: With Universal Hoisting Eye Model IPSBUZ and IPSBUSZ: With Fixed Hoisting Eye

Model	Working Load Limit (t)*	Stock No.	Weight Each (lbs.)	Dimensions (in.)									
				Jaw A	B	C	D	E	F	G	H	J	K
IPSBUUZ	4.5	2705771	34.2	HP 4.00-6.25	4.21	9.92	17.72	2.95	8.11	3.78	3.23	1.42	.79
IPSBUSUZ	4.5	2705772	83.8	HP 7.13-17.00	8.94	16.85	25.00	2.95	14.84	3.74	5.04	-	.79
IPSBUUZ	9	2705773	94.8	HP 4.00-6.25	4.13	10.79	19.33	3.15	9.76	4.84	4.09	1.73	.79
IPSBUSUZ	9	2705774	130	HP 7.13-17.00	8.94	18.82	28.27	3.15	16.73	4.65	6.10	1.73	.98
With fixed hoisting eye													
IPSBUZ	4.5	2705721	29.8	HP 4.00-6.25	4.21	9.92	15.04	2.95	8.11	3.78	3.23	-	.79
IPSBUSZ	4.5	2705722	78.9	HP 7.13-17.00	8.94	16.85	23.31	2.95	14.84	3.74	5.04	-	.79
IPSBUZ	9	2705723	50.7	HP 4.00-6.25	4.13	10.79	18.15	3.15	9.76	4.84	4.09	-	1.18
IPSBUSZ	9	2705724	150	HP 7.13-17.00	8.94	18.82	26.46	3.15	16.73	4.65	6.10	1.77	.98
IPSBUSZ	15	2705728	141	HP 7.13-17.00	8.90	19.09	27.17	3.46	15.79	3.94	5.31	1.93	.98
IPSBUSZ	22.50	2705730	221	HP 7.13-17.00	8.82	21.38	29.13	3.54	18.50	4.57	7.28	-	1.18

* Design Factor based on EN 13155 and ASME B30.20.

