
Grosby Hoist Rings





All Crosby swivel style hoist rings are designed and rated to allow full WLL at 90°, and allow bail to pivot 180° with 360° rotation.

The Crosby Advantage...

Grosby Hoist Rings are:

- 250% proof tested with certification.
- Quenched and Tempered
- All load bearing components contain PIC code for traceability
- Fatigue Rated to 20,000 cycles @ 1.5 WLL
- Top washer Decal contains all necessary ASME B30.26 requirements:
 - ✓ WLL
 - ✓ Required torque
 - ✓ Manufacturer's name and logo

(The above information is also stamped on washer under decal, only available on Crosby hoist rings)

- RFID equipped
- Imperial (Red decal) and Metric (Silver decal) bolt size


Note: Special Hoist Rings available for Subsea and other critical applications.

Special bolt lengths, sizes and finishes are available upon request.









Grosby Hoist Rings VS. Eye bolts

Hoist Rings:

Full WLL in any direction of sling pull. WLL stamped on each Hoist Ring washer. Crosby Hoist Rings can be used in general service conditions in temperatures from -40° F (-40 C) to 400° (204°C). Hoist Ring parts are replaceable.

Eye bolts:

Full WLL only in straight vertical pulls.
Any other angle of pull will result in extreme loss of Rated Working Load.
Eyebolts cannot be repaired.



Direction of Pull (from In-Line)	Adjusted Working Load
45 Degrees	30% - 50% of Rated Working Load
90 Degrees	Consult Manufacturer for Rated Work Load



ASME B30.26-2.6.1.c states:

"When carbon steel eye bolts are to used at temperatures above 275° F (135°C) or below 30°F (-1° C), the manufacturer or a qualified person should be consulted."

Crosby Canada

145 Heart LakeRd.
Brampton, Ontario, Canada L6W 3K3
P: (905) 451-9261
F: (877) 260-5106
sales@crosby.ca

Crosby USA

2801 Dawson Rd., Tulsa, OK 74110 P: (918) 834-4611 F: (918) 832-0940 www.thecrosbygroup.com crosbygroup@thecrosbygroup.com

Crosby Europe

Industriepark Zone b N°26 2220 Heist-op-den-Berg P: (+32) (0)15 75 71 25 F: (+32) (0)15 75 37 64 sales@crosbyeurope.com