



Spectrum 8®
Alloy Chain

- Alloy Steel.
- Heat Treated.
- Finish – Black rust preventative coating.
- Permanently embossed with CG (Crosby Group) and 8 (Grade).
- Proof tested at minimum 2 times the Working Load Limit with certification.
- Standard container:
 - 9/32" to 5/8" in fiber drum
 - 3/4" to 1-1/4" in wooden crate


Grade 80 Alloy Chain Recommended for overhead lifting applications

Chain Size (in)	Chain Size (mm)	Spec. 8 Drum Stock No.	Feet Per Drum / Crate	Material Size (in)	Working Load Limit (lb)*	Maximum Inside Length (in)	Maximum Inside Width (in)	Maximum Length 100 Links (in)	Weight Per 100 Feet (lb)
9/32 (1/4)	7	273527	500	.276	3500	.87	.42	90	72
5/16	8	273536	500	.343	4500	1.01	.49	100	114
3/8	10	273545	500	.394	7100	1.23	.58	125	148
1/2	13	273554	300	.512	12000	1.57	.77	164	243
5/8	16	273563	200	.630	18100	1.93	.90	202	351
3/4	20	1245364	164	.787	28300	2.43	0.98	243	605
7/8	22	1245368	164	.882	34200	2.68	1.08	268	733
1	26	1245376	164	1.06	47700	3.16	1.28	316	1022
1-1/4	32	1245380	82	1.3	72300	3.89	1.57	389	1546


* Proof tested at minimum 2 times Working Load Limit. Ultimate Load is 4 times the Working Load Limit.

Crosby provides two methods of attaching Spectrum 8® chain to Crosby fittings.

CONNECTING AND COUPLER CHAIN LINKS



A-1337
LOK-A-LOY®
Connecting Link
Refer to page 227



S-1325
Grade 100
Coupler Link
Refer to page 237