McKissick® Utility Crane Blocks

380 SERIES HOOK BLOCKS

- · Wide range of product available.
 - Capacity: 5 to 300 Tons Larger Models Available.
 - · Sheave Sizes: 10" to 30".
 - Wireline Sizes: 7/16" to 1-3/8".
- Manufactured by an ISO 9001 and API Q1 certified facilit.
- All single point shank hooks are genuine Crosby®, forged alloy steel, Quenched and Tempered, and have the patented QUIC-CHECK® markings (Duplex hooks are available on all sizes).
- All 380 Blocks are furnished standard with Roller Bearings.
- · Reeving Guide Standard All Models.
- Blocks thru 25 tons use 319N style hooks with S-4320 latches.
- Sheaves lubrication through center pin separate lube channel to each bearing.

- · Sheave fully protected by side plates.
- · Dual action hook (swings and rotates).
- Repair parts available through worldwide distribution network.
- Design Factor of 4:1 (unless otherwise noted).
- All 380 blocks 16" and larger are furnished with McKissick® Roll-Forged sheaves with flame hardened grooves
- "Look for the Orange Hook . . . the mark of genuine McKissick® quality".



OPTIONS AVAILABLE

- · Bronze Bushed Sheaves
- · Duplex Hooks
- · Swivel Tee and Shackle Assemblies
- · Sheave Shrouds
- Anti Rotation Hook Locking Device
- · Plate Steel Cheek Weights
- · Third party testing with Certification available upon request

Dead End Chart (Double, Triple, & Quad Sheave Blocks*)

	Dimensions (in)		Recommended Wedge Socket	
Wireline Size	т	U Hole	McKissick® US-422 / US-422T Utility Socket	
(in)	Thickness	Diameter	Stock No.	Size
7/16	1.00	1.28	1044309+	US4 7/16
1/2	1.00	1.28	1044318+	US4 1/2
9/16	1.00	1.28	1044336+	US5 9/16
5/8	1.00	1.28	1044345+	US5 5/8
3/4	1.25	1.66	1044363+	US6 3/4
7/8	1.25	1.66	1038580	US7 7/8
1	1.25	1.66	1044417+	US8 1
1-1/8	1.75	2.56	1044426+	US10 1-1/8
1-1/4	1.75	2.56	1044435+	US10 1-1/4

^{*} To find Dead End Dimensions for Single Sheave blocks, refer to block tables on pages 313



The patented McKissick Split-Nut® is the standard retention system for standard crane blocks up to 100 Tons.

For custom orders contact our Block Hotline at:

(800) 727-1555 or refer to the special request form on page 453.

⁺ US-422T Terminator Style.