

Swivel Safety Hook BKLK Offshore HDG


Stock No.	Code	WLL (lb) 4:1	WLL (lb) 5:1	L	B	C	E	A	G	H	Weight (lb)
ZG101370	BKLK-13-8 OS W HDG	14800	12000	12.09	2.17	2.83	2.40	0.98	1.18	1.57	10.80
ZG101371	BKLK-16-8 OS W HDG	22600	18000	14.45	2.44	3.46	3.23	1.02	1.46	1.97	18.52
ZG1013561	BKLK-18/20-8 OS W HDG	35300	28300	15.55	2.68	3.46	3.15	1.38	1.81	2.52	29.76
ZG101294	BKLK-22-8 OS HDG	44080	35300	17.17	3.11	3.15	3.15	1.38	1.97	2.44	37.04
ZG101295	BKLK-26-8 OS HDG	60169	47700	19.13	3.94	4.33	4.02	1.77	2.13	2.68	58.42
ZG101344	BKLK-32-8 OS HDG	72300	57745	20.98	4.72	4.33	4.02	1.77	2.44	3.39	71.21
With double latch											
ZGS1167	BKLKD-13-8 OS W HDG	14800	12000	12.09	1.73	2.83	2.40	0.98	1.18	1.57	11.02
ZGS1168	BKLKD-16-8 OS W HDG	22600	18000	14.45	1.89	3.46	3.23	1.02	1.46	1.97	19.40
ZGS1169	BKLKD-18/20-8 OS W HDG	35300	28300	14.49	2.05	2.36	2.83	1.22	1.73	2.56	27.34
GS1170	BKLKD-26-10 OS	60 169	48 048	486	72	110	102	45	54	68	59.52

Manufactured according to requirements in: DNV 2.7-1:2013, DNVGL-ST-0377:2016, DNVGL-ST-0388:2016 and NORSOK R-002:2017.

Safety Hook BK & BKLK Offshore with Double Latch

With recessed trigger

Due to the motion of the sea when loading and unloading offshore, direct impact on the hook could cause the latch to unintentionally open when not being under load, risking the load to unhitch. The double latch safety hook has an extra latch retaining the load in this case.




Stock No.	Code	WLL (lb)*	A	L	B	E	F	G	H	Weight (lb)
Z101154	BKD-13-10	15000	0.79	8.15	1.73	1.77	0.63	1.18	1.57	7.05
Z101155	BKD-16-10	22600	1.02	10.00	1.89	2.20	0.79	1.46	1.97	12.79
Z101156	BKD-18/20-10	35300	1.18	11.42	2.05	2.36	0.87	1.73	2.44	20.06
Z101373	BKD-26-10 OS	60169	1.38	13.58	2.83	3.15	0.98	2.13	2.68	37.04

4:1 Design Factor


Double Latch

Should the hook latch accidentally open, either through direct impact or excessive wear on the trigger, the extra latch is there to retain the load safely. The extra latch is designed to be easily operated.



Recessed Trigger

To avoid the trigger from being hit or damaged it has been recessed into the hook. This prevents the latch further from accidentally opening.



Safety Hook BK Offshore

Stock No.	Code	WLL (lb) 4:1	WLL (lb) 5:1	L	B	E	F	G	H	Weight (lb)
Z101355	BK-26-10 OS	60169	48 048	13.46	3.94	3.15	0.98	2.13	2.68	36.38
Z101364	BK-32-8 OS	72300	57 745	15.75	4.72	3.54	1.18	2.44	3.39	52.03

Offshore material, impact toughness > 20 ft-lb (27 J) at -4°F.

Manufactured according to requirements in: DNV 2.7-1:2013, DNVGL-ST-0377:2016, DNVGL-ST-0388:2016 and NORSOK R-002:2017