


Safety Hook BK HDG

| Stock No. | Code | WLL (lb)* | A | L | B | E | F | G | H | Weight (lb) |
|-----------|--------------|-----------|------|------|------|------|------|------|------|-------------|
| ZG101108 | BK-6-8 HDG | 2500 | 0.47 | 4.29 | 1.14 | 0.87 | 0.39 | 0.59 | 0.83 | 1.10 |
| ZG101097 | BK-7/8-8 HDG | 4500 | 0.55 | 5.43 | 1.46 | 1.10 | 0.43 | 0.67 | 1.02 | 1.98 |
| ZG101024 | BK-10-8 HDG | 7100 | 0.63 | 6.61 | 1.77 | 1.34 | 0.51 | 0.83 | 1.22 | 3.31 |
| ZG101032 | BK-13-8 HDG | 12000 | 0.79 | 8.15 | 2.17 | 1.73 | 0.63 | 1.18 | 1.57 | 6.61 |


4:1 Design Factor



Swivel Safety Hook BKL HDG

| Stock No. | Code | WLL (lb)* | L | B | C | E | A | G | H | Weight (lb) |
|-----------|--------------|-----------|-------|------|------|------|------|------|------|-------------|
| ZG101028 | BKL-10-8 HDG | 7100 | 8.58 | 1.77 | 1.46 | 1.73 | 0.59 | 0.83 | 1.22 | 4.41 |
| ZG101036 | BKL-13-8 HDG | 12000 | 11.10 | 2.17 | 1.93 | 1.89 | 0.75 | 1.18 | 1.57 | 8.82 |
| ZG101044 | BKL-16-8 HDG | 18000 | 13.54 | 2.44 | 2.68 | 2.40 | 0.98 | 1.46 | 1.97 | 16.24 |

4:1 Design Factor



Foundry Hook OKE

| Stock No. | Code | WLL (lb)* | L | B | E | F | G | H | Weight (lb) |
|-----------|----------|-----------|-------|------|------|------|------|------|-------------|
| Z645564 | OKE-32-8 | 72300 | 15.12 | 5.71 | 3.54 | 1.65 | 3.03 | 3.70 | 66.14 |

Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.


4:1 Design Factor



Surface Treatment Production | Växjö, Sweden



Collaborative Robot | Växjö, Sweden



Testing & Inspection | Växjö, Sweden

BEHIND THE SCENES

Get a behind-the-scenes look at the innovative processes to manufacture the world's leading rigging, lifting, and load securement hardware.

Watch all videos at [thecrosbygroup.com/facilities](https://www.thecrosbygroup.com/facilities)