



## A-1346



- Alloy steel — Quenched & Tempered.
- Individually Proof Tested to values shown, with certification.
- Design Factor of 5 to 1.
- Proof Tested with 70% inside width special fixtures sized to prevent localized point loading per EN 1677-4, reference Applications & Warnings.
- Each main link is marked with Product Identification Code (PIC) for material traceability, Grade, CE, chain size and the “CG” (Crosby Group). Each sublink is marked with traceability code.
- A-1346 master links are type approved to DNV Certification. Notes 2.7-1-Offshore Containers. These Crosby master links are 100% proof tested. Every batch is impacted tested. The tests are conducted by Crosby and 3.1 test certification is available upon request.
- Engineered Flat for use with S-1325A coupler link.
- Fatigue rated to 20,000 cycles at 1-1/2 times the Working Load Limit.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these links meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.



5

### Grade 100 A-1346 Welded Master Link Assembly

Stock No.	Weight Each (lb)	Grade 100 Chain Sling Three / Four Legs Chain Size (in)	Grade 80 Chain Sling Three / Four Legs Chain Size (in)	WLL (lb)	Proof Load (lb)	Dimensions (in)							Engineered Flat Size for S-1325A Chain Size (in)
						A	B	C	D	E	F	G	
1256865	2.4	-	6mm	7000	17632	0.51	2.36	4.72	0.51	4.72	2.36	0.26	6mm
1256868	3.5	6mm	6mm	9000	22701	0.67	3.54	6.30	0.51	4.72	2.36	0.26	6mm, 9/32
1256874	3.9	6mm	9/32	9200	23362	0.75	3.54	6.30	0.51	4.72	2.36	0.26	9/32, 5/16
1256878	7.3	5/16, 9/32	5/16	15400	38570	0.87	3.94	7.09	0.67	6.30	3.54	0.33	3/8
1256880	8.9	5/16, 9/32	5/16	15400	38570	0.87	5.71	10.83	0.67	6.30	3.54	0.33	3/8
1256876	8.4	5/16	3/8	18700	46725	0.87	3.94	7.09	0.75	6.30	3.54	0.33	3/8
1256882	10.1	5/16	3/8	19600	49149	0.98	4.53	8.27	0.75	6.30	3.54	0.33	3/8
1256892	11.4	5/16	3/8	19600	49149	0.98	5.71	10.83	0.75	6.30	3.54	0.33	3/8
1256917	15.6	3/8	1/2	31900	80005	1.10	5.71	10.83	0.87	7.09	3.94	0.41	1/2
1256926	21.2	3/8	1/2	37400	93670	1.26	5.71	10.83	0.98	8.27	4.53	0.53	5/8
1256929	28	1/2	5/8	52000	130036	1.42	6.10	11.22	1.10	7.48	4.33	0.53	5/8
1256930	40.6	5/8	5/8	61900	154941	1.57	5.51	10.63	1.26	10.83	5.71	0.66	-
1256953	58.6	5/8	3/4	84400	211143	1.77	7.09	13.39	1.42	11.22	6.10	-	-
1256958	78.2	3/4	7/8	99200	247950	2.01	8.46	15.35	1.57	10.63	5.51	-	-
1256973	134.6	7/8	1	147600	369170	2.17	7.99	15.98	2.01	15.35	8.46	-	-

5:1 Design Factor. Applications with wire rope and synthetic sling generally require a Design Factor of 5. Based on single leg sling (in-line load), or resultant load on multiple legs with an included angle less than or equal to 120 degrees. Proof Test Load equals or exceeds the requirement of ASTM A952(8.1) and ASME B30.9. Chain slings require that the Design Factor be 4:1. Refer to applications & warnings to determine product's actual Ultimate Load. There are no manufactured flats on links over 1 1/4" (32mm).



APPLICATION AND WARNING INFORMATION  
SECTION 17