




S-255



S-255 Spool


- Designed to keep the load centered on the pin, which keeps the sling positioned correctly in the shackle bow.

Working Load Limit (t)	S-255 Stock No.	Weight Each (lb)	Dimensions (in)			
			A	B	C	D
3.25	1020903	.33	1.25	.81	.75	.19
6.5	1020912	.57	1.50	.94	1.00	.25
8.75	1020921	.89	1.75	1.05	1.19	.31
12.5	1020930	1.45	2.00	1.31	1.50	.38
20.5	1020939	2.79	2.50	1.63	1.88	.44
35	1020948	2.40	3.25	2.13	2.25	.50
50	1020957	4.06	3.75	2.38	2.75	.62

* 5:1 Design Factor



S-256



S-256 Link Plate

- Designed to connect two (2) S-252 or S-253 Sling Saver Shackles together.

Working Load Limit (t)	S-256 Stock No.	Weight Each (lb)	Dimensions (in)				
			A	B	C	D	E
3.25	1020785	.83	.75	1.50	3.38	.81	1.88
6.5	1020796	1.62	1.00	1.75	4.12	.94	2.25
8.75	1020807	2.71	1.25	2.00	4.75	1.06	2.62
12.5	1020818	5.18	1.50	2.50	6.00	1.31	3.37
20.5	1020829	8.19	1.75	3.00	7.00	1.62	3.75
35	1020840	17.19	2.00	4.00	9.25	2.12	5.00
50	1020851	37.40	2.88	5.00	10.50	2.38	5.75

* 5:1 Design Factor

