## 380 Series Hook Blocks



- Wide range of products available:
  - 5 to 300 short Tons capacity
  - 10" to 30" sheave diameter
  - 7/16" to 1-3/8" wire rope diameter
  - · Larger capacity blocks available
- All 380 Blocks are furnished standard with roller bearings.
- Reeving Guide Standard all models.
- Blocks through 25 short Tons use 319N style hooks with S-4320 latches.
- Sheaves lubrication through center pin separate lube channel to each bearing.
- Sheave fully protected by side plates.
- Dual action hook (swings and rotates).
- Repair parts available through worldwide distribution network.
- Design Factor of 4:1 (unless otherwise noted).
- All 380 blocks 16" and larger are furnished with McKissick® rollforged sheaves with flame-hardened grooves.
- Marked in short tons unless metric tag requested at time of order.
- Look for the orange hook...the mark of genuine McKissick® quality.





## **OPTIONS AVAILABLE**

- Bronze Bushed Sheaves
- Duplex Hooks
- Swivel Tee and Shackle Assemblies
- Sheave Shrouds
- Anti Rotation Hook Locking Device
- · Plate Steel Cheek Weights
- · Third party testing with Certification available upon request.



Minimized height, for maximum headroom. Traditional guards/guides facilitate reeving without a fitting.

The patented McKissick® Split-Nut® is the standard retention system for standard crane blocks up to 100 Tons.

For standard & custom block orders contact our Block Hotline at 800-727-1555 or visit thecrosbygroup.com/engineeredsolutions for more information.