## 750 Series Bridge Crane Blocks

- · Wide range of products available (see tables below).
- Adjustable sheave spacing in 1/2" increments (1/4" on 6-1/2" size).
- Sheave pitch diameter minimum of 16 times rope diameter on standard sizes.
- All single point shank hooks are genuine Crosby, forged alloy steel, Quenched & Tempered, contain the patented QUIC-CHECK® markings and come with a world class latch that integrates with hook tip.
- Sheave bearings are maintenance free and sealed for life (10,000 hrs).
- · Ability to attach optional anti two-block device.
- Available with shackle as lower connection point.
- · Design Factor of 5 to 1.

Key to McKissick <sup>®</sup> Easy-Lift <sup>®</sup> Overhead Bridge Crane Blocks									
	Single ar Sheave	Double Sheave Blocks Only							
вс	05	D	08	В	36				
	ļ	<b></b>	ļ		<b></b>				
McKissick® 750 Series Bridge Crane Blocks	Working Load Limit (t)	Number of Sheaves S = 1 D = 2	Sheave Diameter (in)	Center Pin Designation	Sheave Spacing in 1/8" Increments				





## **BC-751 Single Sheave**

Model 751 – Single Sheave									
WLL (t)	2	3	5	7.5	10				
Sheave O.D.	6.5" 165mm	8" 203mm	10" 254mm	12" 305mm	14" 356mm				
Pitch Diameter	5.69" 151mm	7.38" 187mm	9.25" 235mm	11" 279mm	12.5" 318mm				
Wire Rope Diameter									
1/4" 6.5mm									
5/16" 8mm									
3/8" 9 - 10mm									
7/16" 11mm									
1/2" 12 - 13mm									
9/16" 14mm									
5/8" 16mm									
3/4" 19mm									
7/8" 22mm									
1" 25 - 26mm									

## **BC-752 Double Sheave**

