



HF-1

- Hay Fork Pulleys with Swivel Hook or Swivel Eye
- Forged steel eyes and hooks.
- Available painted or zinc plated.
- One piece pressed steel shells.
- Edges well rounded to prevent chaffing of rope.
- Can be equipped with hook latch.
- Furnished with roller bearings.
- Pressure lube fittings.
- Natural Rope: Rope constructed of natural or plant based fibers, including manila, hemp, linen, cotton, coir, jute, and sisal.



HF-2

**HF-1 / HF-2 Hay Fork Pulleys with Swivel Hook or Swivel Eye**

Sheave Diameter (in)	Model No.	Hay Fork Pulleys Stock No.		Working Load Limit (short tons)	Wire Rope Diameter (in)	Rope Type	End Fitting	Weight Each (lb)
		Painted	Zinc Plated					
4.5	HF-1	170022	170594	1	1-1/4	Natural Rope	Swivel Hook	6
4.5	HF-2	170086	170629	1	1-1/4	Natural Rope	Swivel Eye	6
4.5	HF-3	170148	170656	1	1/2	Wire Rope	Swivel Hook	6
4.5	HF-4	170200	170683	1	1/2	Wire Rope	Swivel Eye	6
8	HF-5	170264	-	2	1/2	Wire Rope	Swivel Eye	11
6	HF-11	170380	-	2	1-1/2	Natural Rope	Swivel Hook	11
6	HF-12	170442	-	2	1-1/2	Natural Rope	Swivel Eye	11
6	HF-13	170503	-	2	5/8	Wire Rope	Swivel Hook	11
6	HF-14	170567	-	2	5/8	Wire Rope	Swivel Eye	11

4:1 Design Factor.



171

- Steel sheaves with roller bearings and pressure lubrication.
- Forged steel swivel eyes.
- Easy opening feature shown available in 8" size only.

APPLICATION AND WARNING INFORMATION SECTION 17

**171 Tong Block**

Sheave Diameter (in)	Stock No.	Working Load Limit (short Tons)	Wire Rope Diameter (in)	Weight Each (lb)
6	171012	0.5	3/4	11
8	171058	1	3/4	12
10	171101	2.5	3/4	30
12	171156	2.5	3/4	35

4:1 Design Factor.



443

- All steel construction, steel sheaves mounted on roller bearings, grooved for maximum of 3/4" wire rope diameter.
- May be used with three parts of line if utilizing dead end becket.

**443 Lay Down Block**

Sheave Diameter (in)	Stock No.	Working Load Limit (short Tons)	Wire Rope Diameter (in)	Weight Each (lb)
4.5	171414	0.25	1/2	12
6	171432	0.5	3/4	17

4:1 Design Factor.