

**70 Series
Blocks**



McKissick® Oilfield Tubing Blocks

- Manufactured in the USA to API-8C PSL-1 specifications with a minimum design temperature of -4°F (-20°C).
- The 70 Series has a spring loaded hook that is desirable for higher utilization and larger depths. The spring mitigates shock loadings and reduces wear on components.
- The 80 Series is not spring loaded and is desirable for shallow depths and rework.
- Utilizing the McKissick® revolutionary split nut retention system, these critical components:
 - Are precision machined and individually fitted for maximum performance.
 - Eliminate conventional threaded nut and potential problems associated with thread corrosion during regular maintenance.
- Equipped with a duplex hook for easy elevator operation which features:
 - An eight position locking mechanism and rotates on a roller thrust bearing.
 - Locking arms with self-retaining bolts to mitigate drop hazards.
 - Available with optional 35 Ton rod hook clevis.
- McKissick® API-8C sheaves are roll-forged and come equipped with flame hardened grooves for exceptional groove life.
 - Each sheave is individually lubricated from easily accessible lubrication fittings located on the center pin.
 - Equipped with double row tapered roller bearings and seals.
- The E-Z opening roll guards facilitate the fastest possible exposure of sheave cluster for quick reeving and contain no bolts to pull out and lose.
- Engineered for short overall length, extra weight, excellent balance for fast non-wobbling falls.
- Completely streamlined exterior surfaces with no unnecessary projections minimize opportunities for interference during operations.
- Contact the BS&E (Blocks, Sheaves and Engineered Solutions) team for any special requests.
- Email: specials@kitocrosby.com
- Phone: 1-800-777-1555

**80 Series
Blocks**



Fatigue Tested



APPLICATION AND WARNING INFORMATION
SECTION 17

Standard Tubing Block Offerings								
	Series	Number of Sheaves	Block Capacity (Tons)	Sheave Diameter (in)	Nominal Wire Rope Size (in)			
					7/8	1	1-1/8	1-1/4
70 Series	72	2	75	24				
	73	3	75	20				
	73	3	125	24				
	73	3	175	30				
	74	4	175	30				
80 Series	82	2	75	24				
	83	3	75	20				
	83	3	125	24				
	83	3	175	30				
	84	4	125	24				
	84	4	175	30				