

WELL LOGGER'S BLOCKS



475



477



476

- Alloy aluminum housing for maximum strength and minimum weight.
- Extra large double row, pre-adjusted sealed tapered bearing.
- Quick opening pin for fast string-up, light weight for easy handling.



Licensed Under
API Spec. 8C-0021

APPLICATION AND WARNING INFORMATION
SECTION 17

475 / 477 Floor Blocks

Sheave Diameter (in)	Model No.	Floor Block Stock No.	Working Load Limit (short Tons)	Conductor Cable Size (in)	Weight Each (lb)	Connection
7	475	180020	1.5	3/16	10	Swivel Hanger
10	475	180253	2.5	5/16	21	Swivel Hanger
12	475	180440	2.5	5/16	24	Swivel Hanger
14	475	180618	2.5	5/16	43	Swivel Hanger
14	477	169784	6	1/4	58	Swivel Clevis
20	477	191072	6	1/4	70	Swivel Clevis
24	477	191107	10	5/16	130	Swivel Clevis

4:1 Design Factor.

476 Top Blocks

Sheave Diameter (in)	Model No.	Top Block Stock No.	Working Load Limit (short Tons)	Conductor Cable Size (in)	Weight Each (lb)	Connection
7	476	180075	2.5	3/16	10	Stinger Pin
10	476	180333	4	5/16	21	Stinger Pin
12	476	180529	4	5/16	24	Stinger Pin
14	476	180707	4	5/16	43	Stinger Pin

4:1 Design Factor.