

Regular Wood Blocks for Natural Manila Rope

- Hot-dip Galvanized for corrosion resistance.
- Grade 5 bolts secured with lock washers and staked nuts.
- Bronze bushed sheaves with large bearing diameter for extended block life.
- Becketts furnished on all blocks.
- Meets or exceeds all requirements of ASME B30.26. Importantly, these blocks meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.
- Fitting Type: HS-Latch Hook; N-Swivel Hook with Latch; S- Round Pin Anchor Shackles



HS-21-B

21B, 22B, 23B

Block Size (in)	Fitting	Single Sheave 21 B Stock No.	Double Sheave 22 B Stock No.	Triple Sheave 23 B Stock No.
4	HS	603831	604634	605438
5	HS	603859	604652	605456
6	HS	603877	604670	605474
8	HS	603911	604714	605517
4	N	606437	606838	607230
5	N	606455	606856	607258
6	N	606473	606874	607276
8	N	606516	606918	607310
4	S	610039	611635	613232
5	S	610057	611653	613250
6	S	610075	611671	613278
8	S	610119	611715	613312

21B, 22B, 23B

Block Size (in)	Sheave Diameter	Manila Rope Size (in)	Working Load Limit (lb)			Weight Each (lb)		
			21 Single	22 Double	23 Triple	21 Single	22 Double	23 Triple
4	2.25	1/2	1000	1400	1800	1.75	3.00	4.00
5	3.00	5/8	1200	1800	2400	3.25	5.60	6.50
6	3.50	3/4	1800	2400	3200	5.00	8.50	11.50
8	4.75	7/8 - 1	2800	3800	4800	13.00	14.00	21.50

4:1 Design Factor.

Steel Shell Blocks for Natural or Manila Rope

- Hot-dip Galvanized for corrosion resistance.
- Grade 5 bolts secured with lock washers and staked nuts.
- Bronze bushed sheaves with large bearing diameter for extended block life.
- Fitting Type: HS- Latch Hook; N- Swivel Hook with Latch; P- Screw Pin Anchor Shackles



P-303B

301B, 302B, 303B

Block Size (in)	Fitting	Single Sheave 301 B Stock No.	Double Sheave 302 B Stock No.	Triple Sheave 303 B Stock No.
4	HS	680971	681373	681774
6	HS	680999	681391	-
8	HS	681015	681417	681818
4	N	682639	683031	683433
6	N	682675	683077	683479
8	P	691111	692717	694314

APPLICATION AND WARNING INFORMATION SECTION 17

15

301B, 302B, 303B

Block Size (in)	Sheave Diameter	Manila Rope Size (in)	Working Load Limit (lb)			Weight Each (lb)		
			Single	Double	Triple	Single	Double	Triple
4	2.25	1/2	1100	1600	2200	2.25	3.75	5.00
6	3.5	3/4	2000	3300	4000	5.50	9.25	12.50
8	4.75	1	3300	5100	7000	10.00	16.50	22.00

3.5:1 Design Factor.