



**Loose Side Hooks with Latch for Manila Rope**

- Grade 5 bolts secured with lock washers and staked nuts.
- Bronze bushed sheaves with large bearing diameter for extended block life.
- Fitting Type : HS - Latch Hook

**HS-262 Double, HA-261, 262, 263**

Block Size (in)	Fitting	Manila Rope Size (in)	Sheave Diameter	261 B Stock No.	262 B Stock No.	263 B Stock No.	Working Load Limit (lb)			Weight Each (lb)		
							261 Single	262 Double	263 Triple	261 Single	262 Double	263 Triple
4	HS	1/2	2.25	666826	666229	667228	900	1400	1800	1.38	3.21	3.25
5	HS	5/8	3.00	666844	666247	-	1200	1800	-	2.25	3.88	-
6	HS	3/4	3.50	666862	666265	-	1800	2500	-	3.75	6.00	-
8	HS	7/8 - 1	4.75	666906	666309	667308	2800	3800	4800	7.13	10.75	14.75

3:1 Design Factor.

HS-262 Double

APPLICATION AND WARNING INFORMATION SECTION 17



T-350-C

**Gin Blocks for Manila Rope**

- For light hoisting by roofers and contractors.
- Furnished with drop forged swivel latch hooks.
- Equipped with swivel hook with latch.

**350C, 350B, 350R**

APPLICATION AND WARNING INFORMATION SECTION 17

Block Size (in)	Gin Block Stock No.			Sheave Size (in)			Manila Rope Size (in)	Working Load Limit (lb)	Weight Each (lb)
	T-350-B	T-350-R	T-350-C	Outside Diam.	Rim Thickness	Bearing Diam.			
8	710403	710207	710001	8.00	1.25	.75	7/8	1000	9.0
10	710421	710225	710029	10.00	1.25	.88	1	1000	9.8
12	710449	710243	710047	12.00	1.38	.88	1	1000	12.7

3:1 Design Factor.

Bearing Code : B - Self Lubricating Bronze Bushed; R - Roller Bearing; C - Common Iron