



Blocks for Synthetic Fiber Rope with loose swivel hooks

- These blocks are built to carry the increased loads of synthetic fiber ropes.
- Self-lubricated bronze bushed sheaves with large bearing diameter for extended block life.
- Meets or exceeds all requirements of ASME B30.26. Importantly, these blocks meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.
- Fitting Type: S- Round Pin Anchor; N- Swivel Hook Latch

411B, 412B, 413B

Block Size (in)	Fitting	411 B Stock No.	412 B Stock No.	413 B Stock No.
4	S	755105	755301	755506
6	S	755123	755329	755524
4	N	757103	757309	757504
6	N	757121	757327	757522

N-411B

411B, 412B, 413B

Block Size (in)	Fitting	Sheave Diameter	Synthetic Rope Size (in)	Working Load Limit (lb)			Weight Each (lb)		
				Single	Double	Triple	Single	Double	Triple
4	S	2.25	1/2	2000	3000	3000	3.00	4.00	6.00
6	S	3.5	3/4	3000	7000	8000	6.25	10.00	14.00
4	N	2.25	1/2	2000	3000	3000	3.00	4.00	6.00
6	N	3.5	3/4	3000	4000	6000	6.25	10.00	14.00

4:1 Design Factor.

APPLICATION AND WARNING INFORMATION
SECTION 17