

## Marine Block Fitting Codes



**QG**  
Swivel Bolt Type  
Shackle



**QK**  
Upset Swivel  
Bolt Type

## CARGO HOISTING BLOCKS



**E-566**  
with Drilled  
Swivel Eye

- Block is galvanized.
- Blocks 14" and larger have flame-hardened roll forged sheaves that assure greater wire life.
- Roll forged sheave is fitted closely into mortise of shell so wire cannot jam between sheave and shell.
- Available for 3/4" or 1" wire.
- Block is fitted with tapered roller bearings which take both load and side thrusts and hold sheave central so it cannot chafe or wear on the sides.
- Tapered Roller bearing with neoprene seals and stainless steel center pin provide long life and trouble-free service.
- Stainless steel center pin has recessed nuts with lock washers.
- Swivel fitting has permanently sealed thrust bearing.
- Pressure lubrication fittings are standard on both center pin and swivel.
- Individually Proof Tested at 4 times Working Load or 2 times Resultant Load.
- A.B.S. recognized load test certificates are furnished.
- Cargo hoist blocks are rated by the maximum single line pull of the wire rope being used.
- Resultant Load equals 2 times single line pull. Ultimate load equals 5 times the Resultant Load.



**J-566**  
with Oblong  
Swivel Eye

### 566 Hoisting Blocks

APPLICATION AND WARNING INFORMATION  
SECTION 17

Sheave Size (in)	E-566 Stock No.	J-566 Stock No.	QG-566 Stock No.	QK-566 Stock No.	Single Line Pull (short Tons)	Wire Rope Diameter (in)	Weight Each (lb)
12	775003	775209	775806	776002	5	3/4	95
14	775058	775254	775450	775655	5	3/4	100
14	775067	775263	775469	775664	10	1	100
16	776609	776672	776681	776690	10	3/4	130
16	752956	752965	752974	752983	10	1	130

5:1 Design Factor based on Resultant Load. Working Load equals maximum single line pull.