

OVAL PATTERN CONSTRUCTION BLOCKS









- · All blocks are galvanized.
- Assembled with self lubricated bronze bushing.
- Combines weight of regular oval blocks with strength of extra heavy oval blocks.
- · Assembled with bolt type anchor shackle.
- Sheave lubricated through pressure lube fitting in center pin. Side plates are rounded to provide additional stiffness and reduce wear and chaffing of the rope.

Q-681-Z / Q-682-Z / Q-683-Z

Block Size (in)	Stock No.Bronze Bushed Steel Sheaves					
DIOCK Size (III)	Q-681-Z	Q-682-Z	Q-683-Z			
6	760441	760665	-			
6	760452	760676	760812			
8	760463	760687	760823			
10	760474	760698	760834			

Q-681-Z / Q-682-Z / Q-683-Z

Block Size (in)	Sheave Dimensions (in)		Wire Rope	Working Load Limit (short Tons)		Weight Each (lb)				
	Outside Diam.	Rim Thickness	Center Pin Dia.	Diameter (in)	Single	Double	Triple	Single	Double	Triple
6	6	1.00	.75	3/8	3	4	-	15	28	-
6	6	1.00	.75	1/2	3	4	5	16	28	32
8	8	1.25	1.00	5/8	4	6	7	29	43	62
10	10	1.25	1.00	5/8	4	7	8	38	61	80

4:1 Design Factor