

# **Identification of our Master Links**

#### To provide good readability and traceability our master links have the following marking:

#### Product type

**MASTER LINKS** 

- M represents single type master link.
- MT represents master link assembly.

### Size designation

- The size is linked to the WLL as well as to compatible products, like attachment couplers and other components.
- Trade size.
- The size expressed in inch.

## Approved by BG/DGUV

H32 – represents Gunnebo Industries' manufacturing ID. The ID also represents a 3rd part audit by BG in Germany.

#### Traceability code

• The traceability code is unique for the production batch and

normally consists of a letter and a number; for example A2. The traceability code makes it possible to trace and track the product through the whole production process back to the raw material used for the actual product.


#### Gunnebo Sweden

• To clearly highlight the Gunnebo Industries brand, our master links are marked with Gunnebo, Sweden.

#### Meets the standards

• The markings fulfills the requirements of EN 1677-4, ASTM A952 and AS 3775.2.





kitocrosby.com

## **Master Link M**

Stock No.	Code	WLL (t) 5:1		Dimensions (mm)			Weight
		EN 1677-4	A-952/A952M AS 3775.2-2014	L	E	D	(kg)
Z101271	M-6-10	1.5	1.5	100	60	11	0.2
Z100818	M-86-10	2.5	3.2	2.36	60	13	0.4
Z101273	M-108-10	4.0	5.2	140	80	17	0.8
Z101274	M-13-10	6.8	6.8	160	90	19	1.0
Z101267	M-1310-10	7.5	8.0	160	95	22	1.5
Z101268	M-1613-10	10.0	13.6	190	110	28	2.8
Z101247	M-19-10	12.0	16.0	200	120	30	3.5
Z101269	M-2016-10	17.0	20.6	240	140	34	5.2
Z101270	M-2220-10	25.0	30.9	250	150	40	7.3
Z101275	M-2622-10	28.0	32.0	250	150	42	8.7
Z101284	M-32-10	33.0	38.6	340	180	45	12.9
Z101276	M-3226-10	43.0	46.6	300	200	50	14.8
Z101277	M-3632-10	56.0	65.0	350	200	55	20.7
Z101278	M-4536-10	70.0	72.7	375	210	60	26.4
Z101279	M-90T-10	90.0	100.0	450	250	70	42.8
Z101280	M-125T-10*	125.0	125.0	450	260	80	57.0

\* Dimension L and E not acc. to EN 1677-4.

5:1 Design Factor

Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M, AS 3775:2014.