


Sling Hook EGK

For use with Grade 100 or Grade 80 chain. Sling hook with clevis connector.




Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	B	G	H	
Z100915	EGK-6-10	1.5	86	29	17	20	0.4
Z100918	EGK-7-10	2.0	95	32	17	22	0.5
Z100938	EGK-8-10	2.6	95	32	17	23	0.5
Z100942	EGK-10-10	4.0	121	41	23	31	1.0
Z100946	EGK-13-10	6.8	145	49	28	38	2.0
Z100950	EGK-16-10	10.3	170	61	36	46	3.8
Z101138	EGK-20-10	16.0	209	71	42	60	7.3

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Sling Hook EGKN

For use with Grade 100 or Grade 80 chain. Sling hook with latch.




Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	B	G	H	
B14460	EGKN-6-10	1.5	86	25	17	20	0.4
Z100843	EGKN-7-10	2.0	95	27	17	23	0.5
B14461	EGKN-8-10	2.6	95	28	17	23	0.5
B14462	EGKN-10-10	4.0	121	35	23	31	1.1
B14463	EGKN-13-10	6.8	145	42	28	38	2.2
B14464	EGKN-16-10	10.3	170	53	36	46	4.0
Z101127	EGKN-20-10	16.0	209	65	42	60	7.6

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Coupling Link GF – stain proof

High strength stainless steel.




Stock No.	Code	WLL (t)	For chain dim. (mm)	Dimensions (mm)					Weight (kg)
				L	B	F	A	C	
B80202	GF-10-8 SP	3.2	10	68	25	11	13	26	0.3
B80203	GF-13-8 SP	5.4	13	89	30	15	16	33	0.7
B80204	GF-16-8 SP	8.2	16	105	36	19	20	40	1.2

4:1 Design Factor

Coupling Link G HDG

Hot-dip galvanized for marine environments.



Stock No.	Code	WLL (t)	Dimensions (mm)					Weight (kg)
			L	B	F	A	C	
ZG100821	G-6-8 HDG	1.12	45	15	7	8	17	0.1
ZG100822	G-8-8 HDG	2.0	56	18	9	11	22	0.2
ZG100823	G-10-8 HDG	3.2	68	25	11	13	26	0.3
ZG100824	G-13-8 HDG	5.4	89	30	15	16	33	0.7
ZG100825	G-16-8 HDG	8.2	102	36	19	20	40	1.2

4:1 Design Factor