


APPLICATION AND WARNING INFORMATION
SECTION 17

McKissick® Plain Bore Sheaves

- Roll-Forged™ sheaves are available in sizes up to 1981mm diameter.
- McKissick® Plain Bore Sheaves can be equipped with bushings or bearings at an optional charge.
- 356mm diameter sheaves and larger are Roll-Forged with Flame hardened grooves to minimum Rockwell 35C, unless otherwise noted.

"A" Nominal Outside Diameter (mm)	Stock Number	Wire Rope Diameter (mm)	"D" Bore Size (mm)	Hub Width (mm)	Rim Width (mm)	"C" Nominal Hub Outside Diameter (mm)	"B" Nominal Tread Diameter (mm)	Material	Approx. Weight (kg)
76.0	51008	6	19.1	33.3	31.8	28.6	52.5	B.S.	0.45
76.0	11310	10	19.1	33.3	31.8	28.6	52.5	B.S.	0.45
102	51044	6	39.9	25.4	22.2	51.0	79.5	B.S.	0.91
102	1189	10	39.9	25.4	22.2	51.0	79.5	B.S.	0.91
124	2026409	16	44.4	31.8	28.6	57.0	103	F.S.	1.63
149	2023136	19	47.6	44.5	41.3	63.5	111	F.S.	2.72
152	51124	10	41.3	28.6	25.4	57.0	125	F.S.	1.81
152	13014	13	41.3	28.6	25.4	57.0	125	F.S.	1.81
178	51437	6	47.6	34.9	19.1	60.5	159	B.S.	2.81
178	3203	10	47.6	34.9	19.1	60.5	159	B.S.	2.81
203	61710	13	46.9	33.3	31.8	62.0	168	F.S.	3.63
203	2023144	13	47.7	44.5	41.3	65.0	160	F.S.	4.54
203	51598	16	47.6	38.1	34.9	62.0	168	F.S.	3.18
203	2023146	16	47.7	44.5	41.3	65.0	160	F.S.	4.54
203	5194	19	47.6	38.1	34.9	62.0	168	F.S.	3.18
203	2023152	19	47.7	44.5	41.3	65.0	160	F.S.	4.54
203	2023466	26	70.0	63.5	60.5	102	133	F.S.	6.8
216	61747	10	46.9	33.3	25.4	70.0	191	D.I.	4.99
251	51918	10	76.0	44.5	28.6	95.5	217	F.S.	6.35
251	2023154	13	47.6	44.5	41.3	65.0	211	F.S.	6.58
251	6040	13	76.0	44.5	28.6	95.5	217	B.S.	6.35
251	5675	16	34.9	38.1	34.9	82.5	216	F.S.	4.31
251	2023169	16	47.6	44.5	41.3	65.0	211	F.S.	6.58
251	2023173	19	47.6	44.5	41.3	65.0	211	F.S.	6.58
251	2023419	22	63.5	58.5	55.5	89.0	206	F.S.	6.8
254	2023784	28	102	63.5	60.5	146	187	F.S.	12.3
305	2023247	16	47.7	44.5	41.3	82.5	257	F.S.	8.15
305	2023234	19	47.7	44.5	41.3	82.5	248	F.S.	8.15
305	52285	19	76.0	44.5	41.3	114	248	R.F.	7.26
305	2026537	19	76.0	55.5	55.5	114	248	R.F.	10.9
305	62283	22	76.0	55.5	55.5	114	260	R.F.	10.9
305	2030845	26	63.5	58.5	55.5	102	238	R.F.	10.9
330	33653	10	63.5	38.1	28.6	89.0	295	R.F.	6.35
330	50704	13	63.5	38.1	28.6	89.0	295	R.F.	6.35
356	*52720	13	108	63.5	34.9	129	321	D.I.	6.8
356	2023249	16	47.7	44.5	41.3	82.5	308	R.F.	9.07
356	4013098	16	63.5	44.5	41.3	114	308	R.F.	14.1
356	4013187	16	60.5	44.5	41.3	114	308	R.F.	13.6
356	4013105	19	63.5	44.5	41.3	114	299	R.F.	14.1
356	4016503	19	82.5	58.5	55.5	140	299	R.F.	15.4
356	2023564	28	70.0	63.5	60.5	114	289	R.F.	12.7
406	4010046	19	108	70.0	63.5	146	340	R.F.	11.3
406	4010126	26	108	70.0	63.5	146	340	R.F.	19.1
457	4010493	22	89.0	58.7	55.5	140	379	R.F.	29
508	*4014024	8	108	70.0	34.9	146	479	R.F.	20.4
508	4010616	19	89.0	58.5	55.5	140	457	R.F.	29.9
508	4010885	19	108	70.0	54.0	165	457	R.F.	36.3
508	4013613	26	95.0	58.5	55.5	140	419	R.F.	34.5
508	4010625	22	89.0	58.5	55.5	140	430	R.F.	33.6

 Custom sheaves are available.