

SNATCH BLOCK, TAIL BOARD, SINGLE SHEAVE, 2-12t

BLOCKS



- Opening feature permits easy insertion of rope without reeving. Bolt for opening feature is retained, to ensure no lost bolts.
- All sizes feature sheave grooves suited for a range of wireline diameters.
- Meets or exceeds all requirements of ASME B30.26. Importantly, these blocks meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.
- 402 snatch blocks feature a significant reduction in weight compared to snatch blocks made of non-alloy materials.
- Crosby's Engineered Solutions Group is ready to discuss your requirements and help select or develop the ideal block for your application.
- Visit thecrosbygroup.com/engineeredolutions for more information.



APPLICATION AND WARNING INFORMATION SECTION 17

Working Load Limit (t)	Wire Rope Diameter (mm)	Sheave Diameter (mm)	Bearing Code	Weight Each (kg)	Model No.	Stock No.	Dimensions (mm)							
							A	B	C	D	E	F	G	H
2 metric tons														
2	8 - 10	76	BB	1.4	404	102016	124	76	67	26	13	67	22	19.1
4 metric tons														
4	10 - 13	114	BB	3.2	404	102025	197	108	79	40	19	108	41	35.1
5 metric tons														
5	10 - 13 ‡	102	BB	3.2	L-170	599846	213	114	75	40	22	119	57	36.6
5	10 - 13 ‡	102	RB	5.0	L-170	599855	213	114	75	40	22	119	57	36.6
6 metric tons														
6*	10 - 13	127	BB	5.9	L-160	599542	210	130	94	39	19	108	35	36.6
6*	10 - 13	127	RB	5.9	L-160	599551	210	130	94	39	19	108	35	36.6
8 metric tons														
8	16 - 19	152	BB	6.8	404	102098	251	152	106	46	25	130	41	44.5
8	16 - 19	152	RB	6.8	404	102114	251	152	106	46	25	130	41	44.5
8	16 - 19	203	BB	9.5	404	102169	303	206	106	46	25	155	41	44.5
8	16 - 19	203	RB	9.5	404	102187	303	206	106	46	25	155	41	44.5
8	16 - 19	254	BB	13.2	404	102230	356	257	106	46	25	183	43	44.5
8	16 - 19	254	RB	13.2	404	102258	356	257	106	46	25	183	43	44.5
8	16 - 19	305	BB	16.3	404	102301	427	308	106	46	25	229	64	44.5
8	16 - 19	305	RB	16.3	404	102329	427	308	106	46	25	229	64	44.5
12 metric tons														
12*	16 - 19	146	BB	13.2	L-160	599604	253	152	106	44	25	133	47	44.5
12*	16 - 19	146	RB	13.2	L-160	599613	253	152	106	44	25	133	47	44.5
12	19 - 22	152	BB	6.8	402	179238	251	152	106	46	25	130	41	44.5
12	19 - 22	152	RB	6.8	402	179283	251	152	106	46	25	130	41	44.5
12	19 - 22	203	BB	9.5	402	179318	303	206	106	46	25	155	41	44.5
12	19 - 22	203	RB	9.5	402	179363	303	206	106	46	25	155	41	44.5
12	19 - 22	254	BB	13.2	402	179434	356	257	106	46	25	183	43	44.5
12	19 - 22	254	RB	13.2	402	179498	356	257	106	46	25	183	43	44.5

4:1 Design Factor. *3.5:1 Design Factor. ‡ Special Dual Groove Sheave also accepts 32mm Manilla Rope.