

L-320CN
Frame Size D-N



- Available in carbon steel and alloy steel.
- Eye hooks are load rated (marked with the Working Load Limit).
- Fatigue rated to 20,000 cycles at 1.5 times the Working Load Limit.
- Chemical analysis and tensile tests performed on each PIC to verify chemistry and mechanical properties.
- Hooks incorporate QUIC-CHECK® deformation and angle indicators.
(For detailed information, see the Crosby Value Added page at the beginning of this section.)

L-320C
Frame Size O-T



APPLICATION AND WARNING INFORMATION
SECTION 17

L-320N / L-320 Eye Hooks

Working Load Limit (t)		Hook ID Code	Eye Hook Stock No.			Weight Each (kg)	Replacement Latch Kits		
Carbon	Alloy		Carbon L-320C L-320CN S.C.	Carbon GL-320CN Galv.	Alloy L-320A L-320AN S.C.		S-4320 Stock No.	PL Stock No.	SS-4055 Stock No.
0.75	1.25	†D	1022205	1022208	1022380	.28	1096325	-	-
1	1.6	†F	1022216	1022219	1022391	.40	1096374	-	-
1.6	2.5	†G	1022227	1022230	1022402	.65	1096421	-	-
2	3.2	†H	1022238	1022241	1022413	.94	1096468	-	-
3.2	5.4	†I	1022246	1022249	1022424	1.95	1096515	1092000	-
5	8.0	†J	1022260	1022262	1022435	3.76	1096562	1092001	-
7.5	11.5	†K	1022271	1022274	1022446	6.80	1096609	1092002	-
10	16	†L	1022282	1022285	1022457	9.42	1096657	1092003	-
15	22	†N	1022293	1022296	1022468	17.9	1096704	1092004	-
20	31.5	O	1022302	-	1022477	27.2	-	1093716	1090161
25	37	P	1023306	-	1023565	47.6	-	1093717	1090189
30	45	S	1023324	-	1023583	67	-	1093718	1090189
40	60	T	1023342	-	1023609	103	-	1093719	1090205

All carbon hooks have a 5:1 Design Factor. Alloy eye hooks 1t through 22t have a 5:1 Design Factor. Alloy eye hooks 30t through 60t have a 4.5:1 Design Factor. For 3/4t carbon through 22t alloy eye hooks, Proof Load is 2.5 times Working Load Limit. For 20t carbon through 60t alloy eye hooks, Proof Load is 2 times Working Load Limit.